

## BIGFOOT® 4X4 Brushless Officially Licensed Replica (Model 67134-4) Parts List

Parts shown in bold are optional accessories. Part categories and individual part listings are arranged alphabetically.

	<b>Bearings &amp; Bushings</b>	5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/
5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)		axles (2)/ rubber tires (2)
5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)	5186A	Wheels, aluminum (blue-anodized) (2)/ 5x8mm ball bearings (4)/ axles (2)/ rubber tires (2)
5120 5116	Ball bearings, blue rubber sealed (12x18x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)	5186	Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	5186	axles (2)/ rubber tires (2) Wheels, aluminum (red-anodized) (2)/ 5x8mm ball bearings (4)/
5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)		axles (2)/ rubber tires (2)
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	9461X	Wheels, wheelie bar, 6061-T6 aluminum (blue-anodized) (2)/ 5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
1000	Body & Accessories	9461G	Wheels, wheelie bar, 6061-T6 aluminum (green-anodized) (2)/
1926 1726	Antenna caps, vinyl (2)/ antenna spool Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)	04044	5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
3662	Body accessories kit, Bigfoot® No. 1, (includes winch, front and	9461A	Wheels, wheelie bar, 6061-T6 aluminum (orange-anodized) (2)/ 5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
	rear bumpers, roll bar, light bar, engine detail & mounting hardware) (grille sold separately)	9461P	Wheels, wheelie bar, 6061-T6 aluminum (pink-anodized) (2)/ 5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
9048	Body accessories kit, Bigfoot® No. 8 (includes body support, front and rear bumpers, bumper mounts, side skirts (left & right), &	9461R	Wheels, wheelie bar, 6061-T6 aluminum (red-anodized) (2)/ 5x8x2.5mm ball bearings (4)/ o-rings (2)/ 5x8x0.3mm TW (2)
9047	mounting hardware) Body support (for clipless body mounting) (attaches to #9020 body)		Differential Components
3747	Body support (with front & rear latches)/ 2.6x15mm BCS (6) (for	5119	Ball bearings, blue rubber sealed (10x15x4mm) (2)
	clipless body mounting)	5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)
3660X	Body, Bigfoot® No. 1 (clear, requires painting)/ window masks/	5118	Ball bearings, blue rubber sealed (8x16x5mm) (2)
3661-BLUE	decal sheet (requires #3747 body support for clipless mounting) Body, Bigfoot® No. 1, Officially Licensed replica (painted, decals	5381 <b>6780A</b>	Carrier, differential/ x-ring gaskets (2)/ ring gear gasket/ 6x10x0.5 TW Differential kit, center (complete)
0001 BEGE	applied) (assembled with body support for clipless mounting)	6780	Differential kit, center (complete)  Differential kit, center (complete) (aluminum carrier)
9020	Body, Bigfoot® No. 8 (clear, requires painting)/ window masks/	5136X	Differential oil kit (1 each: 10K, 30K, 50K weights)
0000 BLUE	decal sheet (for clipless mounting)	6788	Differential, front (complete with pinion gear and differential
9020-BLUE	Body, Bigfoot® No. 8, Officially Licensed replica, complete (painted, decals applied) (assembled with body support for clipless mounting)		plastics) (fits 1/10-scale Rally & 4X4 VXL models: Slash®,
9047X	Bumper mounts (front & rear)/ side skirts (left & right)	6789	Stampede®, Rustler®) (13/37 ratio)  Differential, rear (complete with pinion gear and differential
9049	Bumpers, front & rear/ bumper cover, front	0.00	plastics) (fits 1/10-scale Rally & 4X4 VXL models: Slash®,
2514	Decal sheet, racing sponsors		Stampede®, Rustler®) (13/37 ratio)
3656 9950	Grille, Bigfoot® No. 1, (chrome)/ decals/ adhesive tape Official Team Traxxas® racing decal set(flag logo/ 6-color)	6882X	Gear set, differential (output gears (2)/ spider gears (2)/ spider gear
9950		6783	shaft, carrier support)  Gear set, differential (spider gears (4)/ spider gear shaft (2))
54404	Center Driveline	6781	Housing, center differential (aluminum)/ x-ring gaskets (2)/ ring
5119A 5119	Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2)		gear gasket (1)/ bushings (4)/ 5x10x0.5 PTW (1)/ 2.5x10 CCS (with
5120	Ball bearings, blue rubber sealed (10x13x4mm) (2)	9081	threadlock) (4) Housing, center differential/ x-ring gaskets (2)/ 5x10x0.5 PTFE-
5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)	3001	coated washer (1)/ 2.5x10 CCS (4)
5117	Ball bearings, blue rubber sealed (6x12x4mm) (2)	6881	Housings, differential, front
9041	Cover, center driveshaft (clear)	6880	Housings, differential, rear
6877 6888	Cover, gear/ motor wire hold-down clip Drive hub, center, rear (1)/ 4x3 GS (1)	6782	Output gears, center differential, hardened steel (2)
6888X	Drive hub, front, hardened steel (1)/ screw pin (1)	5379X <b>5379R</b>	Ring gear, differential/ pinion gear, differential  Ring gear, differential/ pinion gear, differential (machined, spiral
6765	Driveshaft, center, 6061-T6 aluminum (blue-anodized) (189mm)		cut) (front)
6765G 6765A	Driveshaft, center, 6061-T6 aluminum (green-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (orange-anodized)	6879R	Ring gear, differential/ pinion gear, differential (machined, spiral cut) (rear)
	(189mm)	6879	Ring gear, differential/ pinion gear, differential (rear)
<b>6765R</b> 6767	Driveshaft, center, 6061-T6 aluminum (red-anodized) (189mm)		
	Drivoshaft contor plastic (black)/ scrow pin	3965	Screws, 2.5x8mm cap-head machine (6)
	Driveshaft, center, plastic (black)/ screw pin Gear adapter, fixed	3965 1647	Screws, 2.5x8mm cap-head machine (6) Silicone Grease
9090X <b>9090</b>	Driveshaft, center, plastic (black)/ screw pin Gear adapter, fixed Gear adapter, fixed	1647	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  Driveline Components
9090X	Gear adapter, fixed	1647 5119A	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIVA TITLE COMMITTEE  Ball bearings, black rubber sealed (10x15x4mm) (2)
9090X <b>9090</b> 5148 6890	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor	1647 5119A 5119	Screws, 2.5x8mm cap-head machine (6) Silicone Grease
9090X 9090 5148 6890 <b>6890X</b>	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized)	1647 5119A 5119 5116	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIVA ITIA COMMISSION (2) Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2)
9090X 9090 5148 6890 6890X 6890R	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized)	1647 5119A 5119	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  DIVA TO COMMON (1000)  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2)
9090X 9090 5148 6890 <b>6890X</b>	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized)	5119A 5119 5116 <b>9059X</b>	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  Driveline Communities  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or
9090X 9090 5148 6890 6890X 6890R 2575	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6)	5119A 5119 5116 9059X 9057X	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIVE FORMING FO
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6)	5119A 5119 5116 <b>9059X</b> <b>9057X</b> 9057	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIG FORDING FOR
9090X 9090 5148 6890 <b>6890X</b> <b>6890R</b> 2575 2554 3932	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)	5119A 5119 5116 9059X 9057X	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIVE ITIE COMMINITY  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)	5119A 5119 5116 <b>9059X</b> <b>9057X</b> 9057	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITUG III G GOIIII O III S  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft)  Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit)
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  Plassis & Alachmens Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw	5119A 5119 5116 <b>9059X</b> <b>9057X</b> 9057	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIG FOILIDITES  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  Plassis & Attermions  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting)	5119A 5119 5116 9059X 9057X 9057 9051	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITIG FOILIDIGHS  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit)
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040 6724	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  Hassis & Altachments  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting) Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2)	5119A 5119 5116 <b>9059X</b> <b>9057X</b> 9057	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITUA IN HOMINO (2) Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040 6724 6735R	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  HISSIS ATTRIMENTS  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting) Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2) Bumper, front/ skidplate, front (black)	5119A 5119 5116 <b>9059X</b> <b>9057X</b> 9057 9051	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITVG FORDING CONTROLL  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft, center, 6061-T6 aluminum (blue-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (green-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (orange-anodized)
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040 6724	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  Hassis & Altachments  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting) Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2)	5119A 5119 5116 9059X 9057X 9057 9051 9052 6765 6765A	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  ITVA TO HOMINOTES  Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft, center, 6061-T6 aluminum (blue-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (green-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (orange-anodized) (189mm)
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040 6724 6735R 9036 9022 9022-BLK	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  HISSIS ATTRIBUTE  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting) Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2) Bumper, front/ skidplate, front (black) Bumper, rear/ bumper mount, rear/ bumper support, rear Chassis Chassis (black)	5119A 5119 5116 9059X 9057X 9057 9051 9052 6765 6765A 6765R	Screws, 2.5x8mm cap-head machine (6) Silicone Grease    Tiva   Formula   Formula   Formula
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040 6724 6735R 9036 9022 9022-BLK 9023	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  HISSIS ATTERMENT  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting) Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2) Bumper, front/ skidplate, front (black) Bumper, rear/ bumper mount, rear/ bumper support, rear Chassis Chassis (black) Nerf bars, chassis (2)	5119A 5119 5116 9059X 9057X 9057 9051 9052 6765 6765A 6765R 6767	Screws, 2.5x8mm cap-head machine (6) Silicone Grease
9090X 9090 5148 6890 6890X 6890R 2575 2554 3932 1647 5351 9026 9040 6724 6735R 9036 9022 9022-BLK	Gear adapter, fixed Gear adapter, fixed Grease, white lithium Plate, motor Plate, motor, 6061-T6 aluminum (blue-anodized) Plate, motor, 6061-T6 aluminum (red-anodized) Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm caphead machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6) Silicone Grease Slipper pressure plate and hub (alloy)  HISSIS ATTRIBUTE  Battery hold-down (2)/ battery clip/ hold-down post/ screw pin/ pivot post screw Body mounts, front & rear (for clipless body mounting) Box, receiver (sealed)/ foam pad/ 2.5x8mm CS (4)/ 3x10mm CS (2) Bumper, front/ skidplate, front (black) Bumper, rear/ bumper mount, rear/ bumper support, rear Chassis Chassis (black)	5119A 5119 5116 9059X 9057X 9057 9051 9052 6765 6765A 6765R	Screws, 2.5x8mm cap-head machine (6) Silicone Grease  DITICA IN HOMELIAN (2) Ball bearings, black rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (10x15x4mm) (2) Ball bearings, blue rubber sealed (5x11x4mm) (2) Cross pin (2)/ drive pin (2) (repairs 1 axle shaft) Differential output shafts, steel-splined constant-velocity (2) Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit) Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use with #9080 upgrade kit) Driveshaft, center, 6061-T6 aluminum (blue-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (green-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (red-anodized) (189mm) Driveshaft, center, 6061-T6 aluminum (red-anodized) (189mm)

Page 2	BIGFOOT® 4X4 Brushless Officially Licensed Replica: TQ™ 2.4 GHz Radio (Model 67134-4) Parts List	
--------	--	--

Page 2	BIGFOOT® 4X4 Brushless Officially Licensed Repli	ca: TQ™ 2	2.4 GHz Radio (Model 67134-4) Parts List
9052R	Driveshafts, rear, extreme heavy duty, steel-spline constant- velocity with 6mm stub axles (complete assembly) (2) (for use	9080R	Outer Driveline & Suspension Upgrade Kit, extreme heavy duty, red
9055X	with #9080 upgrade kit) Half shaft, external splined (steel-spline constant velocity) (1)	9043	Screw pins, 3x16mm, extreme heavy duty (6) (for use with #9080 upgrade kit)
9056X	Half shaft, internal splined (steel-spline constant velocity) (1)	9038	Shock tower, front, extreme heavy duty, black (for use with #9080
9058X	Rebuild kit, steel-splined constant-velocity driveshafts (includes		upgrade kit)
0050	pins and hardware for one axle shaft)	9038X	Shock tower, front, extreme heavy duty, blue (for use with #9080
9056	Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) (for use with #9080 upgrade kit)	9038-GRAY	upgrade kit) Shock tower, front, extreme heavy duty, gray (for use with #9080 upgrade kit)
9055	Stub axle assembly, rear, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) (for use with #9080	9038G	Shock tower, front, extreme heavy duty, green (for use with #9080 upgrade kit)
9054	upgrade kit) Stub axle, front, 6mm, extreme heavy duty (for use with #9051R	9038T	Shock tower, front, extreme heavy duty, orange (for use with #9080 upgrade kit)
	steel CV driveshafts)	9038R	Shock tower, front, extreme heavy duty, red (for use with #9080
9053	Stub axle, rear, 6mm, extreme heavy duty (for use with #9052R steel CV driveshafts)	9039	upgrade kit) Shock tower, rear, extreme heavy duty, black (for use with #9080
5452X	U-joints, driveshaft (carrier (4)/ 4.5mm cross pin (4)/ 3mm headed pin (4)/ 4x15mm screw pin (2)/ hex pin (2)/ e-clips (6)/ 3x6x0.5 MW (4)) (metal parts for 2 driveshafts)	9039X	upgrade kit) Shock tower, rear, extreme heavy duty, blue (for use with #9080 upgrade kit)
9069	Wheel hubs, 12mm hex (steel), extreme heavy duty (4)/ 2x9.8mm pin	9039-GRAY	Shock tower, rear, extreme heavy duty, gray (for use with #9080
	(4) (for use with #9080 upgrade kit and 6mm axles)  Extreme HD Ungrade Kit	9039G	upgrade kit) Shock tower, rear, extreme heavy duty, green (for use with #9080
9050	Carriers, stub axle, rear, extreme heavy duty, black (left & right)/	9039T	upgrade kit) Shock tower, rear, extreme heavy duty, orange (for use with
	3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)		#9080 upgrade kit)
9050X	Carriers, stub axle, rear, extreme heavy duty, blue (left & right)/ 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	9039R	Shock tower, rear, extreme heavy duty, red (for use with #9080 upgrade kit)
0050 0041	upgrade kit)	9037	Steering blocks, extreme heavy duty, black (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
9050-GRAY	Carriers, stub axle, rear, extreme heavy duty, gray (left & right)/ 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)	9037X	Steering blocks, extreme heavy duty, blue (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
9050G	Carriers, stub axle, rear, extreme heavy duty, green (left & right)/ 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	9037-GRAT	Steering blocks, extreme heavy duty, gray (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
9050T	upgrade kit) Carriers, stub axle, rear, extreme heavy duty, orange (left &	9037G	Steering blocks, extreme heavy duty, green (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
30301	right)/ 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)	9037T	Steering blocks, extreme heavy duty, orange (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
9050R	Carriers, stub axle, rear, extreme heavy duty, red (left & right)/ 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	9037R	Steering blocks, extreme heavy duty, red (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
0022	upgrade kit)	9056	Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) (for use with #9080
9032	Caster blocks (c-hubs), extreme heavy duty, black (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)	9055	upgrade kit) Stub axle assembly, rear, outer, extreme heavy duty (1) (left or right)
9032X	Caster blocks (c-hubs), extreme heavy duty, blue (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)	9054	(assembled with internal-splined half shaft) (for use with #9080 upgrade kit)  Stub axle, front, 6mm, extreme heavy duty (for use with #9051R
9032-GRAY	Caster blocks (c-hubs), extreme heavy duty, gray (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	9053	steel CV driveshafts) Stub axle, rear, 6mm, extreme heavy duty (for use with #9052R steel CV driveshafts)
9032G	upgrade kit) Caster blocks (c-hubs), extreme heavy duty, green (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	9042	Suspension pin set, extreme heavy duty, complete (front and rear) (3x52mm (4), 3x32mm (2), 3x40mm (2)) (for use with #9080 upgrade
9032T	upgrade kit) Caster blocks (c-hubs), extreme heavy duty, orange (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	9042X	kit) Suspension pin set, extreme heavy duty, complete (front and rear) (hardened steel) (3x52mm (4), 3x32mm (2), 3x40mm (2))/
00220	upgrade kit)	9069	M2.5x0.45mm NL (8) (for use with #9080 upgrade kit) Wheel hubs, 12mm hex (steel), extreme heavy duty (4)/ 2x9.8mm pin
9032R	Caster blocks (c-hubs), extreme heavy duty, red (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)		(4) (for use with #9080 upgrade kit and 6mm axles)  Front Suspension & Steering
9057	Differential output yoke assembly, extreme heavy duty (2) (left or right, front or rear) (assembled with external-splined half shaft)	5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)
	(for use with #9080 upgrade kit)	6823 <b>6823G</b>	Bulkhead tie bars, front & rear, aluminum (blue-anodized)  Bulkhead tie bars, front & rear, aluminum (green-anodized)
9051	Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use	<b>6823R</b> 6830X	Bulkhead tie bars, front & rear, aluminum (red-anodized) Bulkhead, front
9052	with #9080 upgrade kit)  Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1)/ screw pin (1) (left or right) (fully assembled, ready to install) (for use	6735 6748-BLK	Bumper, front/ skidplate, front (black) Camber link set (plastic/ non-adjustable) (front &rear) (black)
	with #9080 upgrade kit)	3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,
9051R	Driveshafts, front, extreme heavy duty, steel-spline constant- velocity with 6mm stub axles (complete assembly) (2) (for use with #9080 upgrade kit)	3643G	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, front (TUBES green-anodized, 7075-T6 aluminum,
9052R	Driveshafts, rear, extreme heavy duty, steel-spline constant- velocity with 6mm stub axles (complete assembly) (2) (for use	3643R	stronger than Titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, front (TUBES red-anodized, 7075-T6 aluminum,
9080	with #9080 upgrade kit) Outer Driveline & Suspension Upgrade Kit, extreme heavy duty,	30431	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
9080X	black Outer Driveline & Suspension Upgrade Kit, extreme heavy duty,	9032	Caster blocks (c-hubs), extreme heavy duty, black (left & right)/
9080-GRAY	blue Outer Driveline & Suspension Upgrade Kit, extreme heavy duty,	00207	3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
9080G	gray Outer Driveline & Suspension Upgrade Kit, extreme heavy duty,	9032X	Caster blocks (c-hubs), extreme heavy duty, blue (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
9080T	green Outer Driveline & Suspension Upgrade Kit, extreme heavy duty,		
	orange		

Page 3 BI	IGFOOT® 4X4 Brushless Officially Licensed Replica: TQ™ 2.4 GHz Radio (Model 67134-4) Parts List
-----------	---

9032-GRAY	Caster blocks (c-hubs), extreme heavy duty, gray (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	1589 2745	Double-sided adhesive tape (25mm x 25mm) Nuts, 3mm nylon locking (12)
	upgrade kit)	1747P	Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)
9032G	Caster blocks (c-hubs), extreme heavy duty, green (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)	3647 <b>1747R</b>	Nuts, 4mm flanged nylon locking (steel, serrated) (8)  Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4)
9032T	Caster blocks (c-hubs), extreme heavy duty, orange (left & right)/ 3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	1747G 1747T	Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (orange-anodized) (4)
9032R	upgrade kit) Caster blocks (c-hubs), extreme heavy duty, red (left & right)/	<b>1747A</b> 1985	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4) PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)
9032K	3x32mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080	5525 2742X	Rod ends (12)/ hollow balls (12) Rod ends, short (6)/ hollow balls (6)
9057	upgrade kit) Differential output yoke assembly, extreme heavy duty (2) (left or	3347	Screws, 2.5x5mm button-head machine (hex drive) (6)
3007	right, front or rear) (assembled with external-splined half shaft) (for use with #9080 upgrade kit)	3215 3965	Screws, 2.5x6mm cap-head machine (hex drive) (6) Screws, 2.5x8mm cap-head machine (6)
6845A	Drag link, machined 6061-T6 aluminum (blue-anodized)	2577	Screws, 3x10mm button-head machine (hex drive) (6)
6845G	Drag link, machined 6061-T6 aluminum (green-anodized)	2578	Screws, 3x12mm button-head machine (hex drive) (6)
6845T	Drag link, machined 6061-T6 aluminum (orange-anodized)	2552	Screws, 3x12mm countersunk machine (6) (hex drive)
6845R	Drag link, machined 6061-T6 aluminum (red-anodized)	2579	Screws, 3x15mm button-head machine (hex drive) (6)
9051	Driveshaft assembly, front, extreme heavy duty with 6mm axle (1)/	2586	Screws, 3x15mm cap-head machine (hex drive) (6)
	screw pin (1) (left or right) (fully assembled, ready to install) (for use	3646	Screws, 3x15mm flat-head machine (hex drive) (6)
	with #9080 upgrade kit)	2583	Screws, 3x18 button-head machine (hex drive) (6)
9051R	Driveshafts, front, extreme heavy duty, steel-spline constant-	2580	Screws, 3x20mm button-head machine (hex drive) (6)
	velocity with 6mm stub axles (complete assembly) (2) (for use	2591	Screws, 3x23mm button-head machine (hex drive) (6)
7438	with #9080 upgrade kit)	2582	Screws, 3x30mm button-head machine (hex drive) (6)
7438 9038	Linkage, steering Shock tower, front, extreme heavy duty, black (for use with #9080	2592	Screws, 3x40mm button-head machine (hex drive) (6)
0000	upgrade kit)	2575 2534	Screws, 3x6mm button-head machine (hex drive) (6) Screws, 3x6mm countersunk machine (6) (hex drive)
9038X	Shock tower, front, extreme heavy duty, blue (for use with #9080	3932	Screws, 3x6mm flat-head machine (by (flex drive)  Screws, 3x6mm flat-head machine (hex drive) (6)
	upgrade kit)	2576	Screws, 3x8mm button-head machine (hex drive) (6)
9038-GRAY	Shock tower, front, extreme heavy duty, gray (for use with #9080	1552	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/
	upgrade kit)		wrench
9038G	Shock tower, front, extreme heavy duty, green (for use with	3931	Screws, 3x8mm flat-head machine (hex drive) (6)
	#9080 upgrade kit)	3936	Screws, 4x10mm button-head machine (hex drive) (6)
9038T	Shock tower, front, extreme heavy duty, orange (for use with	3937	Screws, 4x12mm button-head machine (hex drive) (6)
9038R	#9080 upgrade kit) Shock tower, front, extreme heavy duty, red (for use with #9080	2542	Screws, 4x12mm countersunk machine (hex drive) (6)
9030K	upgrade kit)	3938	Screws, 4x14mm button-head machine (hex drive) (6)
6845X	Steering bellcranks/ servo saver/ servo saver spring/ servo spring	2546	Screws, 4x15mm countersunk machine (hex drive) (6)
00.071	retainer/servo horn, steering	2743	Set (grub) screws, 3mm hardened (12)
9037	Steering blocks, extreme heavy duty, black (left & right)/ 3x20mm	3642X	Shoulder screws, Ultra Shocks (3x12 hex drive) (6)
	BCS (2) (for use with #9080 upgrade kit)	2754	Stub axle pins (4)
9037X	Steering blocks, extreme heavy duty, blue (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)	2746	Washers, 3x6mm metal (12)  Motors & Electronics
9037-GRAY	Steering blocks, extreme heavy duty, gray (left & right)/ 3x20mm BCS	1726	Antenna, tube (1)/ vinyl antenna cap (1)/ wire retainer (1)
	(2) (for use with #9080 upgrade kit)	2260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input
9037G	Steering blocks, extreme heavy duty, green (left & right)/	2200	voltage)
	3x20mm BCS (2) (for use with #9080 upgrade kit)	3382	BL-2s™ Brushless Power System, waterproof (includes BL-2s™ ES
9037T	Steering blocks, extreme heavy duty, orange (left & right)/		& BL-2s™ 3300 motor)
9037R	3x20mm BCS (2) (for use with #9080 upgrade kit)	3383	BL-2s™ Electronic Speed Control, waterproof (brushless)
9037K	Steering blocks, extreme heavy duty, red (left & right)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)		(fwd/rev/brake)
9056	Stub axle assembly, front, outer, extreme heavy duty (1) (left or right) (assembled with internal-splined half shaft) (for use with #9080	3340	Cooling fan, electronic speed control, Velineon® VXL-3s or BL- 2s™
	upgrade kit)	9090X	Gear adapter, fixed
3655P	Suspension arms, blue, front/rear (left & right), heavy duty (2)	9090	Gear adapter, fixed
3655R	Suspension arms, front/rear (left & right), heavy duty (2)	2072A	Gear set (for 2070, 2075 servos)
3655G	Suspension arms, green, front/rear (left & right), heavy duty (2)	2072X 2252	Gear set, metal (for 2070, 2075 servos)
3655T	Suspension arms, orange, front/rear (left & right), heavy duty (2)	2252 2272	Gear set, metal (for 2250, 2255 servos) Gear set, metal (for 2270 waterproof servo)
3655L	Suspension arms, red, front/rear (left & right), heavy duty (2)	2272	Gear set, metal (for 2270 water proof servo)
9042	Suspension pin set, extreme heavy duty, complete (front and rear) (3x52mm (4), 3x32mm (2), 3x40mm (2)) (for use with #9080 upgrade	<b>2072R</b> 6860A	Gear set, metal, high-speed (for 2070, 2075 servos)  Motor mount (assembled with 3x6 flat-head machine screw)/ 3.0mm
9042X	kit) Suspension pin set, extreme heavy duty, complete (front and	6860R	NL (1) Motor mount, 6061-T6 aluminum (blue-anodized)
	rear) (hardened steel) (3x52mm (4), 3x32mm (2), 3x40mm (2))/	6890	Plate, motor
6740	M2.5x0.45mm NL (8) (for use with #9080 upgrade kit)	6890X	Plate, motor, 6061-T6 aluminum (blue-anodized)
6742	Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center)	6890R	Plate, motor, 6061-T6 aluminum (red-anodized)
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)	3347 3932	Screws, 2.5x5mm button-head machine (hex drive) (6) Screws, 3x6mm flat-head machine (hex drive) (6)
6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger	2254	Servo case, aluminum (middle) (blue-anodized) (for 2250 servo)
6742R	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger	2253 2251	Servo case, aluminum (middle) (red-anodized) (for 2255 servo) Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (fo
	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1) Turnbuckles, camber link, 49mm (82mm center to center)	2271	2250, 2255 servos) Servo case/ gaskets (for 2270 waterproof servo)
3643		2074	Servo case/gaskets (for 2056 and 2075 waterproof servos) Servo, digital high-speed, metal gear (ball bearing), waterproof
	(assembled with rod ends and hollow balls) (1 left, 1 right)  Turnbuckles, camber link, 91mm (80mm center to center)	2075P	oci vo, uigitai migni-speeu, metai year (bali bearing), waterproof
	Turnbuckles, camber link, 91mm (80mm center to center)	<b>2075R</b> 2075	Servo digital high-torque (hall hearing) waterproof
3643 9031 5539	Turnbuckles, camber link, 91mm (80mm center to center) (assembled with rod ends and hollow balls) (2) Turnbuckles, camber links, 58mm (assembled with rod ends and	<b>2075R</b> 2075 <b>2250</b>	Servo, digital high-torque (ball bearing), waterproof Servo, digital high-torque 330 coreless, metal gear (ball bearing waterproof
9031	Turnbuckles, camber link, 91mm (80mm center to center) (assembled with rod ends and hollow balls) (2)	2075	Servo, digital high-torque 330 coreless, metal gear (ball bearing waterproof Servo, digital high-torque 400 brushless, metal gear (ball
9031	Turnbuckles, camber link, 91mm (80mm center to center) (assembled with rod ends and hollow balls) (2) Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)	2075 <b>2250</b>	Servo, digital high-torque 330 coreless, metal gear (ball bearing waterproof

## Page 4 BIGFOOT® 4X4 Brushless Officially Licensed Replica: TQ™ 2.4 GHz Radio (Model 67134-4) Parts List

2270 2075X	Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof		Ready-To-Race Model
350R	Velineon® VXL-3s Brushless Power System, waterproof	67134-4	Bigfoot® 4X4 Brushless: 1/10-scale 4WD Monster Truck with TQ
	(includes VXL-3s waterproof ESC , Velineon® 3500 motor, and		2.4GHz radio system
	speed control mounting plate (part #3725))		Rear Suspension
	Radio System, Batteries & Chargers	6823	Bulkhead tie bars, front & rear, aluminum (blue-anodized)
327X	3000mah 7.4v 2-Cell LiPo Battery	6823G 6823R	Bulkhead tie bars, front & rear, aluminum (green-anodized) Bulkhead tie bars, front & rear, aluminum (red-anodized)
923X	3000mAh 8.4V 7-cell flat NiMH Battery, Power Cell	6829	Bulkhead, rear
940X	3300mAh 8.4V 7-cell flat NiMH Battery, Series 3 Power Cell	6748-BLK	Camber link set (plastic/ non-adjustable) (front &rear) (black)
950X 960X	4200mAh 8.4V 7-cell flat NiMH Battery, Series 4 Power Cell 5000mAh 8.4V 4-cell flat NiMH Battery, Series 5 Power Cell	3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum
843X	5800mah 7.4v 2-Cell 25C LiPo Battery		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
869X	7600mah 7.4v 2-Cell 25C LiPo Battery		wrench (1) (#2579 3x15 BCS (4) required for installation)
976	AC to DC adapter	3644G	Camber links, rear (TUBES green-anodized, 7075-T6 aluminus stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum
938X	Adapter, Traxxas® iD® LiPo battery (adapts Traxxas® iD®		wrench (1) (#2579 3x15 BCS (4) required for installation)
	batteries to separate balance ports)	3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum,
<b>943</b> 548	Battery charge indicators, green (4), grey (4), blue (4) Battery door, TQ 2.4 transmitter (replacement for #6516, 6517 transmitter)		stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
914	Battery, Power Cell AA Alkaline (4)	9050	Carriers, stub axle, rear, extreme heavy duty, black (left & rig 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080
985-2S	Battery/charger completer pack (includes #2985 charger (1),		upgrade kit)
	#2827X 3000mAh 7.4V 2-cell 20C LiPo iD® Battery (1))	9050X	Carriers, stub axle, rear, extreme heavy duty, blue (left & righ
260	BEC assembly (complete) (12.6 volts (3s LiPo) maximum input voltage)		3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
975 972	Charger, D/C, 4 amp (6 - 7 cell, 7.2 - 8.4 volt, NiMH)	9050-GRAY	Carriers, stub axle, rear, extreme heavy duty, gray (left & right)/
972 973	Charger, EZ-Peak Dual, 100W, NiMH/LiPo with iD Auto Battery Identification Charger, EZ-Peak Live Dual, 200W, NiMH/LiPo with iD Auto	9050G	3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)  Carriers, stub axle, rear, extreme heavy duty, green (left & rig
970	Battery Identification Charger, EZ-Peak Plus, 4 amp, NiMH/LiPo with iD Auto Battery	9050G	Sax41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 upgrade kit)
981	Identification Charger, EZ-Peak® Plus 4s, 8 amp, NiMH/LiPo with iD® Auto	9050T	Carriers, stub axle, rear, extreme heavy duty, orange (left & right)/ 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with
	Battery Identification		#9080 upgrade kit)
985	Charger, EZ-Peak®, USB-C, 40W, NiMH/LiPo with iD® Auto Battery Identification	9050R	Carriers, stub axle, rear, extreme heavy duty, red (left & right 3x41mm hinge pins (2)/ 3x20mm BCS (2) (for use with #9080 transfer bit)
1 <b>78</b> 172A	Fuse, D/C charger, 5A (2) (for #2974, 2975, 2977) Gear set (for 2070, 2075 servos)	9057	upgrade kit) Differential output yoke assembly, extreme heavy duty (2) (left or
72X	Gear set, metal (for 2070, 2075 servos)	3037	right, front or rear) (assembled with external-splined half shaft) (for
252	Gear set, metal (for 2250, 2255 servos)		use with #9080 upgrade kit)
72	Gear set, metal (for 2270 waterproof servo)	9052	Driveshaft assembly, rear, extreme heavy duty with 6mm axle (1).
72R	Gear set, metal, high-speed (for 2070, 2075 servos)		screw pin (1) (left or right) (fully assembled, ready to install) (for u
)68X	LiPo cell voltage checker/balancer (includes #2938X adapter for Traxxas® iD® batteries)	9052R	with #9080 upgrade kit)  Driveshafts, rear, extreme heavy duty, steel-spline constant- velocity with 6mm stub axles (complete assembly) (2) (for us
168	LiPo cell voltage checker/balancer (requires #2938X adapter for Traxxas® iD® batteries)	9039	with #9080 upgrade kit) Shock tower, rear, extreme heavy duty, black (for use with #9080
<b>35</b> 19	Mount, temperature sensor (electric motors)/ wire tie/ thermal pad Receiver, micro, TQ 2.4GHz (3-channel)	9039X	upgrade kit) Shock tower, rear, extreme heavy duty, blue (for use with #90
33	Receiver, micro, TQi 2.4GHz with telemetry & TSM® (5-channel)		upgrade kit)
32	Screws, 3x6mm flat-head machine (hex drive) (6)	9039-GRAY	Shock tower, rear, extreme heavy duty, gray (for use with #90
21	Sensor, temperature and voltage (long)	9039G	upgrade kit)
254	Servo case, aluminum (middle) (blue-anodized) (for 2250 servo)	9039G	Shock tower, rear, extreme heavy duty, green (for use with #8 upgrade kit)
253	Servo case, aluminum (middle) (red-anodized) (for 2255 servo)	9039T	Shock tower, rear, extreme heavy duty, orange (for use with
51	Servo case, plastic (top, middle, bottom)/ gaskets/ hardware (for		#9080 upgrade kit)
74	2250, 2255 servos)	9039R	Shock tower, rear, extreme heavy duty, red (for use with #908
2 <b>71</b> )74	Servo case/ gaskets (for 2270 waterproof servo) Servo case/gaskets (for 2056 and 2075 waterproof servos)		upgrade kit)
775R	Servo, digital high-speed, metal gear (ball bearing), waterproof	8338	Shock towers, front & rear
75	Servo, digital high-torque (ball bearing), waterproof	9055	Stub axle assembly, rear, outer, extreme heavy duty (1) (left or rig (assembled with internal-splined half shaft) (for use with #9080
50	Servo, digital high-torque 330 coreless, metal gear (ball bearing),		upgrade kit)
	waterproof	3655P	Suspension arms, blue, front/rear (left & right), heavy duty (2
255	Servo, digital high-torque 400 brushless, metal gear (ball	3655R	Suspension arms, front/rear (left & right), heavy duty (2)
75X	bearing), waterproof	3655G	Suspension arms, green, front/rear (left & right), heavy duty (
175X 270	Servo, digital high-torque, metal gear (ball bearing), waterproof Servo, digital high-torque, metal gear (ball bearing), waterproof	3655T	Suspension arms, orange, front/rear (left & right), heavy duty
609R	TQi 2.4 GHz High Output radio system, 2-channel, Traxxas® Link enabled, TSM® (2-ch transmitter, 5-ch micro receiver)	<b>3655L</b> 9042	Suspension arms, red, front/rear (left & right), heavy duty (2) Suspension pin set, extreme heavy duty, complete (front and real (3-52)mm (4), 3-22)mm (2), 3-40 mm (2)), (for use with #0000 users
07R	TQi 2.4 GHz High Output radio system, 4-channel with Traxxas® Link Bluetooth® module, TSM® (4-ch transmitter, 5-ch micro receiver)	9042X	(3x52mm (4), 3x32mm (2), 3x40mm (2)) (for use with #9080 upgr kit) Suspension pin set, extreme heavy duty, complete (front and rear) (hardened steel) (3x52mm (4), 3x32mm (2), 3x40mm (2))
16	Transmitter, TQ 2.4GHz, 2-channel (transmitter only)		M2.5x0.45mm NL (8) (for use with #9080 upgrade kit)
28	Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 2-	3644	Turnbuckles, camber link, 39mm (69mm center to center)
29	channel (transmitter only) Transmitter, TQi Traxas® Link enabled, 2.4GHz high output, 3-		(assembled with rod ends and hollow balls) (1 left, 1 right) (fi front & rear on Slash, rear on Slash 4X4)
530	channel (transmitter only) Transmitter, TQi Traxxas® Link enabled, 2.4GHz high output, 4- channel (transmitter only)	5031	Shock 01 Oil, shock (20 wt, 200 cSt, 60cc) (silicone)
511	channel (transmitter only) Traxxas® Link Bluetooth® module	5031	Oil, shock (30 wt, 350 cSt, 60cc) (silicone)
	HUAAUSE LIIIK DIUGIOOIIIE IIIOUUIE		
		5033	Oil, shock (40 wt, 500 cSt, 60cc) (silicone)

Page 5	BIGFOOT® 4X4 Brushless Officially Licensed Repli	ca. i d	214 Onz Radio (model of 104-4) Faits Elst
5035	Oil, shock (60 wt, 700 cSt, 60cc) (silicone)	6863	Springs, front (progressive, +10% rate, pink) (2)
5036	Oil, shock (70 wt, 900 cSt, 60cc) (silicone)	6864	Springs, front (progressive, +20% rate, blue) (2)
5037	Oil, shock (80 wt, 1,000 cSt, 60cc) (silicone)	6862	Springs, front (progressive, -10% rate, green) (2)
5029 5038X	Shock oil bottle (60cc) (for mixing shock oil) Shock oil set (includes 20 wt, 30 wt, 40 wt, 50 wt, 60 wt, 70 wt, &	6861 6857	Springs, front (progressive, -20% rate, orange) (2) Springs, front (white) (progressive rate) (2)
3030A	80 wt premium shock oils with spinning carousel rack)	6867	Springs, front (write) (progressive rate) (2) Springs, rear (progressive, +10% rate, pink) (2)
5038	Spinning carousel rack	6868	Springs, rear (progressive, +20% rate, blue) (2)
	Shocks (GTR)	6866	Springs, rear (progressive, -10% rate, green) (2)
7466X	Body, GTR long (hard-anodized, PTFE-coated aluminum) (1)	6865	Springs, rear (progressive, -20% rate, orange) (2)
7466-PINK	Body, GTR long (pink-anodized, PTFE-coated aluminum) (1)	6858	Springs, rear (white) (progressive rate) (2)
7466	Body, GTR long shock, aluminum (blue-anodized) (PTFE-coated		Shocks (Ultra Shocks)
	bodies) (1)	3765A	Body, Ultra Shock (long) (grey) (2)
7466G	Body, GTR long shock, aluminum (green-anodized) (PTFE-	3766A	Body, Ultra Shock (XXL) (grey) (2)
7466A	coated bodies) (1) Body, GTR long shock, aluminum (orange-anodized) (PTFE-	5475	Multi-tool (plastic)
74000	coated bodies) (1)	1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws (2)
7466R	Body, GTR long shock, aluminum (red-anodized) (PTFE-coated	2742X	Rod ends, short (6)/ hollow balls (6)
	bodies) (1)	3767	Shock caps (2)/ shock bottoms (2)
7467X	Body, GTR xx-long (hard-anodized, PTFE-coated aluminum) (1)	8361	Shock caps (black) (4) (assembled with hollow balls)
7467-PINK 7467	Body, GTR xx-long (pink-anodized, PTFE-coated aluminum) (1) Body, GTR xx-long shock, aluminum (blue-anodized) (PTFE-	3767A	Shock caps, aluminum (blue-anodized) (4) (fits all Ultra Shocks)
1401	coated bodies) (1)	3767G	Shock caps, aluminum (green-anodized) (4) (fits all Ultra Shocks)
7467G	Body, GTR xx-long shock, aluminum (green-anodized) (PTFE-	3767T	Shock caps, aluminum (orange-anodized) (4) (fits all Ultra Shocks)
	coated bodies) (1)	3767P	Shock caps, aluminum (pink-anodized) (4) (fits all Ultra Shocks)
7467A	Body, GTR xx-long shock, aluminum (orange-anodized) (PTFE-	3767X	Shock caps, aluminum (red-anodized) (4) (fits all Ultra Shocks)
7467R	coated bodies) (1) Body, GTR xx-long shock, aluminum (red-anodized) (PTFE-	1664T	Shock shafts, hardened steel, titanium nitride coated (long) (2)
1401K	coated bodies) (1)	2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)
7468	Caps and spring retainers, GTR long/xx-long shock (upper cap	1664	(2) Shock shafts steel shrome finish (long) (2)
	(2)/ hollow balls (4)/ bottom cap (2)/ upper retainer (2)/ lower	<b>1664</b> 2656	Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2)
<b>-</b> 400	retainer (2))	1765	Silicone diaphragms (4)
7463	Rebuild kit, GTR long/xx-long shocks (x-rings, bladders, pistons, piston nuts, shock rod ends, hollow balls) (renews 2 shocks)	3769	Spring pre-load spacers: 1mm (4)/ 2mm (2)/ 4mm (2)/ 8mm (2)
5469	Rod ends (GTR shocks)	3768	Spring retainers, upper & lower (2)/ piston head set (2-hole (2)/ 3-hole
7464T	Shaft, GTR long, TiN-coated (2)		(2))
7465T	Shaft, GTR xx-long, TiN-coated (2)	3758	Springs (front) (2)
7461	Shocks, GTR long blue-anodized, PTFE-coated bodies with TiN	3758T 3757T	Springs, blue (front) (2) Springs, blue (rear) (2)
74040	shafts (fully assembled, without springs) (2)	6863	Springs, fine (rear) (2) Springs, front (progressive, +10% rate, pink) (2)
7461G	Shocks, GTR long green-anodized, PTFE-coated bodies with TiN shafts (fully assembled, without springs) (2)	6864	Springs, front (progressive, +20% rate, blue) (2)
7461X	Shocks, GTR long, hard-anodized, PTFE-coated bodies with TiN	6862	Springs, front (progressive, -10% rate, green) (2)
	shafts (assembled) (2) (without springs)	6861	Springs, front (progressive, -20% rate, orange) (2)
7462	Shocks, GTR xx-long blue-anodized, PTFE-coated bodies with	6857	Springs, front (white) (progressive rate) (2)
7462G	TiN shafts (fully assembled, without springs) (2) Shocks, GTR xx-long green-anodized, PTFE-coated bodies with	3758A 3757A	Springs, green (front) (2) Springs, green (rear) (2)
7402G	TiN shafts (fully assembled, without springs) (2)	3757A	Springs, green (rear) (2) Springs, pink (front) (2)
7462X	Shocks, GTR xx-long, hard-anodized, PTFE-coated bodies with	3757P	Springs, pink (rear) (2)
	TiN shafts (assembled) (2) (without springs)	6867	Springs, rear (progressive, +10% rate, pink) (2)
7440	Spring, shock, white (GTR long) (0.623 rate orange) (1 pair)	6868	Springs, rear (progressive, +20% rate, blue) (2)
7441	Spring, shock, white (GTR long) (0.653 rate green) (1 pair)	6866	Springs, rear (progressive, -10% rate, green) (2)
7444 7445	Spring, shock, white (GTR long) (0.767 rate black) (1 pair) Spring, shock, white (GTR long) (0.810 rate pink) (1 pair)	6865 6858	Springs, rear (progressive, -20% rate, orange) (2)
7448	Spring, shock, white (GTR long) (0.892 rate blue) (1 pair)	3758X	Springs, rear (white) (progressive rate) (2) Springs, white (front) (2)
7442	Spring, shock, white (GTR xx-long) (0.711 rate orange) (1 pair)	3757X	Springs, white (rear) (2)
7443	Spring, shock, white (GTR xx-long) (0.762 rate green) (1 pair)	3760	Ultra Shocks (black) (long) (complete w/ spring pre-load spacers
7446	Spring, shock, white (GTR xx-long) (0.874 rate black) (1 pair)		& springs) (front) (2)
7447	Spring, shock, white (GTR xx-long) (0.884 rate pink) (1 pair)	3762	Ultra Shocks (black) (xx-long) (complete w/ spring pre-load
7449	Spring, shock, white (GTR xx-long) (1.004 rate blue) (1 pair)	37604	spacers & springs) (rear) (2)
	Shocks (Pro-level Aluminum)	3760A	Ultra Shocks (gray) (long) (complete w/ spring pre-load spacers & springs) (2)
5862	Big Bore shocks (hard-anodized & PTFE-coated T6 aluminum)	3762A	Ultra Shocks (grey) (xx-long) (complete w/ spring pre-load spacers &
2000	(assembled with TiN shafts and springs) (front & rear) (4)		springs) (rear) (2)
2660	Big-bore shocks (long) (hard-anodized & PTFE-coated T6 aluminum) (assembled with TiN shafts) w/o springs (2)		Slipper Clutch Components
2662	Big-bore shocks (xx-long) (hard-anodized & PTFE-coated T6	5119A	Ball bearings, black rubber sealed (10x15x4mm) (2)
	aluminum) (assembled with TiN shafts) w/o springs (rear) (2)	6893X	Bearing adapter, 6061-T6 aluminum (blue-anodized)
2669	Piston head set (2-hole (2)/ 3-hole (2))/ shock mounting bushings		(1)/10x15x4mm ball bearing (black rubber sealed) (1) (for slipper
1040	& washers (2) (Big Bore Shocks)	60020	shaft)
1942	Rod ends (16 long & 4 short)/ hollow ball connectors (18)/ ball screws	6893G	Bearing adapter, 6061-T6 aluminum (green-anodized) (1)/ 10x15x4mm ball bearing (black rubber sealed) (1) (for slipper
2742X	(2) Rod ends, short (6)/ hollow balls (6)		shaft)
2667	Shock caps, aluminum (2) (Big Bore Shocks)	6888	Drive hub, center, rear (1)/ 4x3 GS (1)
2362	Shock rebuild kit (for 2 shocks)	6888X	Drive hub, front, hardened steel (1)/ screw pin (1)
1664T	Shock shafts, hardened steel, titanium nitride coated (long) (2)	6883	Gear set, center differential (output gears (2)/ spider gears (2)/
2656T	Shock shafts, hardened steel, titanium nitride coated (xx-long)	6004	spider gear shaft)
	(2)	6884	Housing, center differential/ x-ring gaskets (2)/ ring gear gasket/ bushings (2)/ 5x10x0.5 TW (2)/ CCS 2.5x8 (4)
1664			
1664 2656	Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2)	6893	Input shaft (slipper shaft)/ bearing adapter (1)/ pin (1)
1664 2656 1765	Shock shafts, steel, chrome finish (long) (2) Shock shafts, steel, chrome finish (xx-long) (2) Silicone diaphragms (4)	6893 5352R	Rebuild kit (heavy duty), slipper clutch (steel disc/ aluminum friction
2656	Shock shafts, steel, chrome finish (xx-long) (2)		, , , , , , , , ,

Page 6	BIGFOOT® 4X4 Brushless Officially Licensed Repl	ica: TQ™ 2	2.4 GHz Radio (Model 67134-4) Parts List
5352X	Rebuild kit, slipper clutch (steel disc/ friction pads (3)/ spring (1)/ 2x9.8mm pin/ 5x8mm MW/ 5.0mm NL (1)/ 4.0mm NL (1))	9950 9909	Official Team Traxxas® racing decal set(flag logo/ 6-color) Traxxas® racing banner, red & black (3x7 feet)
2554	Screws, 3x6mm caphead machine (hex drive) (6)		Tires & Wheels
5351	Slipper pressure plate and hub (alloy)	5116	Ball bearings, blue rubber sealed (5x11x4mm) (2)
	Spur Gears & Pinion Gears	9075	Center caps, wheel (black) (4)
6877	Cover, gear/ motor wire hold-down clip	1747P	Nuts, 4mm flanged nylon locking (aluminum, pink anodized) (4)
9090	Gear adapter, fixed	3647	Nuts, 4mm flanged nylon locking (steel, serrated) (8)
9090X 6746	Gear adapter, fixed Gear, 10-T pinion (32-p) (steel) (fits 3mm shaft)/ set screw	1747R 1747G	Nuts, aluminum, flanged, serrated (4mm) (blue-anodized) (4) Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)
6745	Gear, 9-T pinion (32-p) (steel) (fits 3mm shaft)/ set screw	1747G 1747T	Nuts, aluminum, flanged, serrated (4mm) (green-anodized) (4)
3956	Spur gear, 54-tooth (0.8 metric pitch, compatible with 32-pitch)	1747A	Nuts, aluminum, flanged, serrated (4mm) (red-anodized) (4)
6842X	Spur gear, steel, 50-tooth (0.8 metric pitch, compatible with 32-	1985	PTFE-coated Washers, 5x8x0.5mm (20) (use with ball bearings)
3956X	pitch) (for center differential) Spur gear, steel, 54-tooth (0.8 metric pitch, compatible with 32-	1647 2754	Silicone Grease Stub axle pins (4)
	pitch) (for center differential)	4175	Tires & wheels, assembled, glued (2.8") (All-Star black chrome
	Steering Components		wheels, paddle tires, foam inserts) (nitro rear/electric front) (2)
5114	Ball bearings, blue rubber shield (5x8x2.5mm) (2)	3669A	(TSM® rated)
6845A	Drag link, machined 6061-T6 aluminum (blue-anodized)	3003A	Tires & wheels, assembled, glued (2.8") (All-Star black chrome wheels, Talon tires, foam inserts) (nitro rear/electric front) (2)
6845G 6845T	Drag link, machined 6061-T6 aluminum (green-anodized)		(TSM® rated)
6845R	Drag link, machined 6061-T6 aluminum (orange-anodized) Drag link, machined 6061-T6 aluminum (red-anodized)	3669	Tires & wheels, assembled, glued (2.8") (All-Star chrome wheels,
7438	Linkage, steering	6792	Talon tires, foam inserts) (nitro rear/electric front) (2) Tires & wheels, assembled, glued (black 2.8" wheels,
2742X	Rod ends, short (6)/ hollow balls (6)	****	Sledgehammer® tires, foam inserts) (2) (TSM® rated)
1552	Screws, 3x8mm cap-head machine (hex drive) (6)/washers (6)/	9072	Tires & wheels, assembled, glued (black chrome 2.8" wheels,
6845X	wrench Steering bellcranks/ servo saver/ servo saver spring/ servo spring retainer/servo horn, steering	9072-GRAY	Sledgehammer® tires, foam inserts) (2) (TSM® rated) Tires & wheels, assembled, glued (charcoal gray 2.8" wheels,
6742	Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center)	3665X	Sledgehammer® tires, foam inserts) (2) (TSM® rated) Tires & wheels, assembled, glued (chrome wheels, Terra Groove dual profile tires, foam inserts) (nitro rear/ electric front) (2)
6742X	Toe links (TUBÉS blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)	3665	Tires & wheels, assembled, glued (satin chrome wheels, Terra Groove dual profile tires, foam inserts) (nitro rear/ electric front)
6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)	3663-WHT	(2) Tires & wheels, assembled, glued (white wheels, Terra Groove dual
6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)	6771	profile tires, foam inserts) (2)  Tires & wheels, assembled, glued 2.8" (All-Star chrome wheels,
2746	Washers, 3x6mm metal (12)	6769	Maxx® tires, foam inserts) (2)
	Suspension Linkage	6772	Tires, Talon EXT 2.8" (2)/ foam inserts (2) Wheels, RXT 2.8" (black) (2)
2537 6748-BLK	3mm threaded rods (includes 1 each of 20mm, 25mm & 44mm)	3664-WHT	Wheels, white, dual profile (2.0" outer 3.0" inner) (2)
3643X	Camber link set (plastic/ non-adjustable) (front &rear) (black)  Camber links, front (TUBES blue-anodized, 7075-T6 aluminum,		Traxxas Tools
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum	3433X	Body reamer (aluminum handle)
20420	wrench (1) (#2579 3x15 BCS (4) required for installation)	3433	Body reamer (plastic handle)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than Titanium) (83mm) (2)/ rod ends (4)/ aluminum	3436	Cap, body reamer
	wrench (1) (#2579 3x15 BCS (4) required for installation)	3432 3431	Scissors, curved tip Scissors, straight tip
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum,	8712	Speed Bit Essentials Set, hex and nut driver, 7-piece, includes
	stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)		premium handle (medium), travel pouch, hex drivers (straight:
3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum,		1.5mm, 2.0mm, 2.5mm) and nut drivers (5.0mm, 5.5mm, 7.0mm, and 8.0mm), 1/4" drive
	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum	8720	Speed bit handle, large (overmolded)
3644G	wrench (1) (#2579 3x15 BCS (4) required for installation) Camber links, rear (TUBES green-anodized, 7075-T6 aluminum,	8721	Speed bit handle, medium (one piece)
00440	stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum	8722	Speed bit handle, premium (rubber overmold)
	wrench (1) (#2579 3x15 BCS (4) required for installation)	8710	Speed Bit Master Set, hex and nut driver, 13-piece, includes premium handle (medium), travel pouch, hex drivers (straight:
3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum		1.5mm, 2.0mm, 2.5mm, 3.0mm), (ball-end: 2.0mm, 2.5mm, 3.0mm), and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm,
5525	wrench (1) (#2579 3x15 BCS (4) required for installation) Rod ends (12)/ hollow balls (12)		8.0mm), 1/4" drive
3739	Screw pin set (Rustler®/ Bandit/ Stampede®)	8711	Speed Bit Master Set, hex driver, 7-piece straight and ball end, includes premium handle (medium), travel pouch, hex drivers
6834	Suspension pin set, complete (front and rear)		(straight: 1.5mm, 2.0mm, 2.5mm, 3.0mm) (ball end: 2.0mm,
6742	Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center)	8719	2.5mm, 3.0mm), 1/4" drive Speed Bit Master Set, nut driver, 6-piece, includes premium
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)		handle (medium), travel pouch, and nut drivers (4.0mm, 4.5mm, 5.0mm, 5.5mm, 7.0mm, 8.0mm), 1/4" drive
6742G 6742R	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1) Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger	8716	Speed Bit Set, hex driver, 2-piece ball-end (2.0mm, 2.5mm), 1/4" drive
	than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)	8716X	Speed Bit Set, hex driver, 3-piece ball-end (2.0mm, 2.5mm, 3.0mm) 1/4" drive
3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash)	8715	Speed Bit Set, hex driver, 3-piece straight (1.5mm, 2.0mm, 2.5mm), 1/4" drive
3643	Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right)	8715X 8714	Speed Bit Set, hex driver, 4-piece straight (1.5mm, 2.0mm, 2.5mm, 3.0mm), 1/4" drive Speed Bit Set, screwdriver, 3-piece straight (3mm slotted, #1
9031	Turnbuckles, camber link, 91mm (80mm center to center)	31 14	Phillips, and #2 Phillips bits), 1/4" drive
	(assembled with rod ends and hollow balls) (2)	2748R	Tool set (includes 1.5mm hex wrench / 2.0mm hex wrench / 2.5mm hex wrench / 4 way wronch / 8mm % 4mm wronch / H. joint

**Team Traxxas Items** 

Decal sheet, racing sponsors

Backpack, RC car carrier, 12" x 12" x 24" (fits TRX-4 & similar)

Duffel bag, medium, 30" x 12" x 12" (fits 1/10 Slash®, TRX-4®, & similar)

9916

2514

9917

2.5mm hex wrench/ 4-way wrench/ 8mm & 4mm wrench/ U-joint

wrench)

## Page 7 BIGFOOT® 4X4 Brushless Officially Licensed Replica: TQ™ 2.4 GHz Radio (Model 67134-4) Parts List

3415	Tool set with pouch (includes 1.5mm, 2.0mm, 2.5mm, 3.0mm,
	3.5mm, 4mm drivers/4mm. 5mm, 5.5mm, 7mm, and 8mm nut
	drivers/ 2mm, 3mm, and 4mm slotted screwdrivers/ #00 Phillips,
	#0 Phillips, and #1 Phillips screwdrivers/ 4mm and 8mm
	wrenches/ driver handle)

	wrenches/ driver nandle)
	Turnbuckles & Threaded Rods
3643X	Camber links, front (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3643G	Camber links, front (TUBES green-anodized, 7075-T6 aluminum, stronger than Titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3643R	Camber links, front (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (83mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3644X	Camber links, rear (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3644G	Camber links, rear (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
3644R	Camber links, rear (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (73mm) (2)/ rod ends (4)/ aluminum wrench (1) (#2579 3x15 BCS (4) required for installation)
5525	Rod ends (12)/ hollow balls (12)
6742	Toe link, front & rear (molded composite) (2)/ hollow balls (4) (87mm center to center)
6742X	Toe links (TUBES blue-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
6742G	Toe links (TUBES green-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
6742R	Toe links (TUBES red-anodized, 7075-T6 aluminum, stronger than titanium) (87mm) (2)/ rod ends (4) aluminum wrench (1)
3644	Turnbuckles, camber link, 39mm (69mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right) (fits front & rear on Slash)
3643	Turnbuckles, camber link, 49mm (82mm center to center) (assembled with rod ends and hollow balls) (1 left, 1 right)
9031	Turnbuckles, camber link, 91mm (80mm center to center) (assembled with rod ends and hollow balls) (2)
5539	Turnbuckles, camber links, 58mm (assembled with rod ends and hollow balls) (2)

If you have questions or need technical assistance, call Traxxas at:

## 1-888-TRAXXAS

(1-888-872-9927) (U.S. residents only)

For orders, calls outside the U.S., and other information, call 972-549-3000, or fax to 972-549-3011 e-mail Traxxas at support@Traxxas.com

TRAXXAS.COM